


The superior IT rack monitoring The KENTIX MultiSensor-LAN with E-Mail and SNMP



Surveillance and monitoring of all risk in IT racks and server rooms
with the innovative Kentix MultiSensor LAN



- Early detection of all risks ■
- Real time alarming via e-mail or SNMP ■
- Configuration and handling with integrated web server ■
- Plug'n Play installation due to PoE ■



KENTIX
Innovative Security



MultiSensor LAN
High-White

MultiSensor LAN
Carbon-Black

LAN

only 90x90x45mm!

The KENTIX MultiSensor detects all threats in room and rack!



Temperature



Humidity



Dew point




Motion detection



Fire
carbon monoxide (CO)



Leakage (Optional)



External signal inputs



External alarm I/O
outputs

Data sheet

Functions

All in one sensor system with LAN Anschluss (PoE) and integrated web server. For stand alone usage with e-mail alarming or in connection with a network monitoring software with SNMP interface.

Room size

It-rack or it-room up to 20 sq. m. per MultiSensor.

Configuration

HTTP-Server with authentication, visualization
NTP-Client for time synchronization.

Reports

E-Mail (ESMTP) with authentication for up to 5 recipients
SNMP V2 Traps (threshold, cold start, registration)
SNMP GET, access to measurements (MIB download)
SNMP SET, change of states (MIB download)

Temperature

0 bis 99°C measuring range

Humidity

0 bis 100% relative humidity

Dew point

Dew point determination with temperature and rel. humidity

Fire (CO)

carbon monoxide measurement >10ppm, alarm threshold can be defined from 10 - 200ppm. (operate in generator facilities)

Buzzer

Internal buzzer 85dB/1m, 2,3kHz

Motion

PIR sensor, detection angle 110°, range approx. 12m, rooms up to 20 - 25 sq. m.

Connection

LAN 10/100MBit with PoE (IP V4/V6)
Kentix system jack for ext. extensions. (leakage sensor)
Internal terminal for digital I/O extensions.
Connection of S0-power meter possible. (optional)

Externe digital I/O

2 digital alarm input (potential free contacts)
2 digital Open-Collector switch outputs (100mA)

LED

RUN (yellow) and ALARM (red)

Order information

MultiSensor-LAN (Carbon-Black)
MultiSensor-LAN (High-White)
Leakage sensor with accessories

Order no.

KMS-LAN-B
KMS-LAN-W
KLS02P

price €

475,00
475,00
160,00